



NOTES:

- 1. ALLOWABLE OPTICAL MATERIAL:  
SCHOTT: ZERODUR 542/562
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO < 3 ARCMIN
- 3. COATING (APPLY ACROSS COATING APERTURE)  
  
S1: PROTECTED GOLD  
Ravg ≥ 94% 700-800nm @ 0° AOI  
Ravg ≥ 97% 800-2,000nm @ 0° AOI

- S2: NONE
- 4. ARROW ON EDGE POINTING TOWARDS SURFACE S1.
- 5. FINE GROUND SURFACE



**FOR INFORMATION ONLY:**  
**DO NOT MANUFACTURE PARTS TO THIS DRAWING**

	S1	S2	EFL (AT 587.6nm)	NA	 Edmund Optics®	
SHAPE	PLANO	PLANO				
SURFACE ACCURACY AT 632.8nm	1/10 WAVE	NA	BFL (AT 587.6nm)	NA	TITLE	1/10λ Optical Flat, Zerodur, 4inch Diameter PROTECTED GOLD
SURFACE QUALITY	60 - 40	COMMERCIAL POLISH				
CLEAR APERTURE	Ø 91.4	Ø 91.4	ALL DIMS IN	mm	DWG NO	31392-566
BEVEL MAX FACE	1.0 x 45°	1.0 x 45°				