NOTES:


- SUBSTRATE: FUSED SILICA
- 2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN < 10 ARCMINS
- 3. COATING(APPLY ACROSS CLEAR APERTURE)

 METALLIC BASED ND, OPTICAL DENSITY (abs) = 1.0 ± 10% FROM 700 1100nm





FINE GROUND SURFACE

- 5. POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICATIONS APPLY ACROSS CLEAR APERTURE
- 6. ROHS COMPLIANT



PARTS TO THIS DRAWING





IR NEUTRAL DENSITY FILTER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

S1 BLANC	S2	_			Edmund Option	CS®
PLANO	PLANO					
3 - 5λ	3 - 5λ		1		OD 1 Ø12 5mm NIR ND FILTER	
40-20	40-20	THIRD ANGLE PROJECTION	TITLE	OD 1, Ø12.5IIIII, NIK NO HEIEK		
Ø10.0	Ø10.0		1			CHEET
PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	47827	SHEET 1 OF
	40-20 Ø10.0	S1 S2 PLANO PLANO 3 - 5λ 3 - 5λ 40-20 40-20 Ø10.0 Ø10.0	S1 S2 PLANO PLANO 3 - 5λ 3 - 5λ 40-20 40-20 Ø10.0 Ø10.0	S1 S2 PLANO PLANO 3 - 5λ 3 - 5λ 40-20 40-20 Ø10.0 Ø10.0	S1 S2 PLANO PLANO	S1 S2 Edmund Option S2 Edmund Option S2 Edmund Option S3 - 5λ S3 - 5λ S4 -