

NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH \$1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) S1 & S2: RAVG ≤0.5% @ 600 - 1050nm



- 5. Rohs Compliant
- 6. SURFACE FLATNESS (P-V): $\lambda/4$ (per inch over clear aperture)







PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2
SHAPE	PLANO	PLANO
SURFACE QUALITY	60-40	60-40
CLEAR APERTURE	Ø11.25	Ø11.25
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED

			Edmund Optics ®	
THIRD ANGLE PROJECTION	\$	TITLE	12.5mm DIA., 3mm THICK, NIR I COATE N-BK7 WINDOW	D λ/4
ALL DIMS IN	mm	DWG NO	83468	SHEET 1 OF

12.5mm D	IA., 3mm THICK, NIR I COATED λ/4
	N-BK7 WINDOW

SHEET 1 OF 1