
NOTES:


- 1. SUBSTRATE: N-BK7
- 2. S2 TO BE PARALLEL WITH S1 TO <1 ARCMIN
- 3. COATING (APPLY ACROSS CLEAR APERTURE) \$1 & \$2: R(AVG) ≤1.75% @ 400 - 700nm




5. RoHS COMPLIANT

6. SURFACE FLATNESS (P-V): $\lambda/4$ (per inch over clear aperture)







FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	S2		
SHAPE	PLANO	PLANO		
SURFACE QUALITY	60-40	60-40		
CLEAR APERTURE	67.50 x 67.50	67.50 x 67.50		
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED		

			Edmund Optics®		
	THIRD ANGLE PROJECTION		TITLE	75mm Sq, 4mm THICK,, MgF2 COATED λ/4 N-BK7 WINDOW	
D	ALL DIMS IN	mm	DWG NO	62609	SHEET 1 OF 1