## NOTES:


- SUBSTRATE: Float Glass
- 2. COATING (APPLY ACROSS CLEAR APERTURE)
  S1: Protected Silver (450-10000nm)
  R(AVG) >98% @ 450 800nm
  R(AVG) >98.5% @ 2000 10,000nm


S2: NONE



EDGES SEAMED

4. Rohs Compliant





## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHAPE	S1 PLANO	S2 PLANO			R	<b>Edmund Optics</b>	<b>S</b> ®
SURFACE QUALITY	60-40	N/A		I		50 x 50mm Silver, 4-6λ Mirror	
SURFACE FLATNESS	4 - 6λ	N/A	THIRD ANGLE PROJECTION		TITLE	30 X 3011111 311VC1, 4-0X WIIITOI	
CLEAR APERTURE	47.50 x 47.50	N/A					CLIEFT
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	89495	SHEET 1 OF 1