## NOTES:

SUBSTRATE MATERIAL:
 FUSED SILICA

2. CENTERING TOLERANCE (AT 587.6nm):
PLANO AXIS WEDGE: < 5 ARCMIN
POWER ASIX WEDGE: < 5 ARCMIN
AXIAL TWIST: < 3 ARCMIN

3. COATING (APPLY ACROSS CLEAR APERTURE)


\$1 & \$2: R(AVG) ≤0.4% FROM 425-675nm @ 0° AOI


4.


FINE GROUND SURFACE

 POWER, IRREGULARITY, AND SURFACE QUALITY SPECIFICAIONS APPLY ACROSS CLEAR APERTURE

6. ROHS COMPLIANT







## FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

						Edmund Ontice®	
	\$1	\$2				Edmund Optic	,5°
SHAPE	CONVEX	PLANO		1			
SURFACE QUALITY	40 - 20	40 - 20	THIRD ANGLE PROJECTION		TITLE	LENS CYL SHAPING 25.4mm SQ x 75mm VIS 0	
CLEAR APERTURE	22.86 x 22.86	22.86 x 22.86		1			CUEET
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED	ALL DIMS IN	mm	DWG NO	36100	SHEET 1 OF 1