NOTES:

SUBSTRATE:
FUSED SILICA


2. COATING (APPLY ACROSS COATING APERTURE):


\$1:  $R(AVG) \ge 98\%$  @ 340-488nm @ 0° AOI  $R(AVG) \ge 98\%$  @ 320-450nm @ 45° AOI FOR ALL POLARIZATION  $R(AVG) \ge 98\%$  @ 320-450nm @ 45° FOR S-POLARIZATION

S2: NONE

3. FINE GRIND SURFACE







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

SHAPE	S1 PLANO	S2 PLANO			8	Edmund Option	CS®
CLEAR APERTURE	> 90	N/A	THIRD ANGLE PROJECTION		TITLE	Ø5mm, 320 - 450nm BROADBAND λ/10 MIRROR	
SURFACE QUALITY	20-10	COMMERCIAL POLISH					
SURFACE FLATNESS	λ/10 (BEFORE COATING)	N/A					CHEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	37558	SHEET 1 OF 1