NOTES:

1. SUBSTRATE:

HOYA GLASS: ND-40


FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING


2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN <0.02 mm




4. COATING SPECIFICATION:S1 & S2:R(AVG) ≤0.5% @ 600 - 1050nm

- 5. OPTICAL DENSITY: 0.4 +/-0.05 @400-700nm
- 6. TRANSMISSION (%): 40.0% AVERAGE FROM 400-700nm
- 7. ROHS COMPLIANT







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

E Edmund C)ptics®
-------------------	---------

	S1	S2		TITLE	0.4 OD, 25mm DIA., NIR I COATED, ABSORPTIVE ND FILTER		
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION				
SURFACE QUALITY	80-50	80-50		I		7.555.11.11.2.12	OUEET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	13167	SHEET 1 OF 1