NOTES:

1. SUBSTRATE:

HOYA GLASS: ND-0.3


2. SURFACE S2 TO BE PARALLEL WITH SURFACE S1 TO WITHIN < 0.02mm


FOR INFORMATION ONLY: DO NOT MANUFACTURE PARTS TO THIS DRAWING




4. COATING SPECIFICATION:S1 & S2:R(AVG) ≤0.5% @ 600 - 1050nm

- 5. OPTICAL DENSITY: 2 +/-0.3 @ 400-700nm
- 6. TRANSMISSION (%): 1.0% AVERAGE FROM 400-700nm
- 7. ROHS COMPLIANT







SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

|--|

	S1	S2		1		2.0 OD, 50mm DIA., NIR I COATED	,
SHAPE	PLANO	PLANO	THIRD ANGLE PROJECTION		TITLE	ABSORPTIVE ND FILTER	
SURFACE QUALITY	80-50	80-50		1		7.2001	- OLIFET
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED	ALL DIMS IN	mm	DWG NO	13192	SHEET 1 OF 1